

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name ENi55-FCG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Arc Welding

1.3. Details of the supplier of the safety data sheet

Supplier WELDING MATERIAL SALES

Street address 3940 Stern Ave St. Charles IL 60174

 Telephone
 +I 630-232-6421

 Email
 sales@weldingmaterialsales.com

 Web site
 www.weldingmaterialsales.com

1.4. Emergency telephone number

Emergency phone number +1 800-424-9300

Available outside office hours Yes

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Description The product is not classified as hazardous according to applicable GHS hazard classification criteria.

2.2. Label elements

The product does not require labelling in accordance with CLP Regulation (EC) No 1272/2008.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

2.3. Other hazards	
Other hazards	This product contains nickel, which is classified as a skin sensitizer and a suspect carcinogen. In the form that nickel is present in this product it does not contribute to a hazard classification of the product. Skin contact is normally no hazard but should be avoided to prevent possible allergic reactions. Persons with a pacemaker should not go near welding or cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device. When this product is used in a welding process, the most important hazards are welding fumes, heat, radiation and electric shock. Fumes: Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eyes. Chronic overexposure to welding fumes may affect pulmonary function. Prolonged inhalation of nickel compounds above safe exposure limits can cause cancer. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait. Heat: Spatter and melting metal can cause burn injuries and start fires. Radiation: Arc rays can severely damage eyes or skin. Electricity: ELECTRIC SHOCK can kill.
Other	

Other Emergency Overview: Metal wire or rods in varying colours. This product is normally not considered hazardous as shipped. Gloves should be worn when handling to prevent cuts and abrasions.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-phrase M factor acute M factor chronic	Note
IRON(REACh Registered)	7439-89-6 231-096-4 - -	50 - 60%	-	-	-
Nickel powder**	7440-02-0 231-111-4 - -	39 - 45%	Skin Sens. 1, Carc. 2, STOT RE 1, Aquatic Chronic 3	H317, H351, H372, H412 - -	-
CARBON	7440-44-0 231-153-3 - -	1.5 - 2.5%	-	-	-
MAGNESIUM	7439-95-4 231-104-6 - -	0.3 - 1%	-	-	-
Silicon	7440-21-3 231-130-8 - -	0 - 1%	-	-	-
MANGANESE	7439-96-5 231-105-1 - -	0.1 - 0.7%	-	-	-
Potassium Silicofluoride	16871-90-2 240-896-2 - -	0 - 0.3%	Acute Tox. 3 - dermal	H311 - -	-
ALUMINUM	7429-90-5 231-072-3 - -	0 - 0.2%	-	-	-

Product based on This product is a preparation of core wire with extruded coating.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

Nicore 55

SECTION 4: First aid measures

4.1. Description of first aid mea	sures
Description of first aid measures	Electric shock: Disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live parts or wires. If not breathing, begin artificial respiration, preferably mouth-to-mouth. If no detectable pulse, begin Cardio Pulmonary Resuscitation (CPR). call emergency physician to the scene of the accident.
Inhalation	If breathing has stopped, perform artificial respiration and obtain medical assistance immediately! If breathing is difficult, provide fresh air and call physician.
Skin contact	For skin burns from arc radiation, promptly flush with cold water. Get medical attention for burns or irritations that persist. To remove dust or particles wash with mild soap and water
Eye contact	For radiation burns due to arc flash, see physician. To remove dusts or fumes flush with water for at least fifteen minutes. If irritation persists, obtain medical assistance.
4.2. Most important symptoms	and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media No specific recommendations for welding consumables. Welding arcs and sparks can ignite combustible and flammable materials. Use the extinguishing media recommended for the burning materials and fire situation.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for firefighters

Special protective equipment for Wear self-contained breathing apparatus as fumes or vapors may be harmful. **fire-fighters**

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions, protective equipment and emergency procedures

Wear hand, head, eyes, ear and body protection like welders gloves, helmet or face shield with filter lens, safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

6.2. Environmental precautions

Environmental precautions Refer to section 13.

6.3. Methods and material for containment and cleaning up

Methods and material for Solid objects may be picked up and placed into a container. Liquids or pastes should be scooped up and placed into a container while handling these materials. Do not discard as refuse.

6.4. Reference to other sections

Reference to other sections Refer to section 8/13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions Handle with care to avoid stings and cuts. Wear gloves when handling welding consumables. Avoid exposure to dust. Do not ingest. Some individuals can develop an allergic reaction to certain materials. Retain all warning and identity labels.

7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, Keep separate from chemical substances like acids and strong bases, which could cause chemical reactions.

7.3. Specific end use(s)

Specific end use(s) Arc Welding

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits Use industrial hygiene monitoring equipment to ensure that exposure does not exceed applicable national exposure limits. The following limits can be used as guidance. Unless noted, all values are for 8 hour time weighted averages (TWA).

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Ceiling exposure limit ppm / mg/m³	Source	Remark	Year
MANGANESE	7439-96-5 231-105-1	-	- 5	OSHA	as Mn (metal and fume)	2019
Silicon	7440-21-3 231-130-8	- 15	-	OSHA	Total dust	2019
ALUMINUM	7429-90-5 231-072-3	- 15	-	OSHA	total dust	2019
Potassium Silicofluoride	16871-90-2 240-896-2	-	-	OSHA		2019
IRON(REACh Registered)	7439-89-6	-	-	OSHA	No PEL	2019

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m³	Ceiling exposure limit ppm / mg/m³	Source	Remark	Year
	231-096-4	-	-			
CARBON	7440-44-0 231-153-3	-	-	OSHA	NO PEL	2019
Silicon	7440-21-3 231-130-8	- 5	-	OSHA	Respirable fraction	2019
ALUMINUM	7429-90-5 231-072-3	- 5	-	OSHA	respirable fraction	2019
Nickel Powder**	7440-02-0 231-111-4	- 1	-	OSHA ·	as Ni	2019
Nickel powder**	7440-02-0 231-111-4	- 1.5	-	ACGIH	elemental	2019
Nickel powder**	7440-02-0 231-111-4	- 0.1	- -	ACGIH	soluble inorganic compounds	2019
MANGANESE	7439-96-5 231-105-1	- 0.02	-	ACGIH	as Mn	2019
MAGNESIUM	7439-95-4 231-104-6	-	-	OSHA	NO PEL	2019
MAGNESIUM	7439-95-4 231-104-6	-	-	ACGIH	-	2019
IRON (REACh Registered)	7439-89-6 231-096-4	-	-	ACGIH	-	2019
Nickel powder**	7440-02-0 231-111-4	- 0.2	-	ACGIH	insoluble inorganic compounds	2019
CARBON	7440-44-0 231-153-3	- -	-	ACGIH	-	2019
MANGANESE	7439-96-5 231-105-1	- 0.1	-	ACGIH	for elemental and inorganic compounds	2019
SILICON	7440-21-3 231-130-8	-	-	ACGIH	-	2019
ALUMINUM	7429-90-5 231-072-3	- 1	-	ACGIH	Respirable fraction	2019
Potassium Silicofluoride	16871-90-2 240-896-2	-	-	ACGIH	-	2019

8.2. Exposure controls

Hand protectionAbrasion (Cycles):(Type A-2 (500));(Type B-1 (100)); Cut (Factor):(Type A-1 (1.2));(Type B-1 (1.2)); Tear
(Newton):(Type A-2 (25));(Type B-1 (10)); Puncture (Newton):(Type A-2 (60));(Type B-1 (20)); Burning
Behaviour:(Type A-3);(Type B-2); Contact Heat:(Type A-1);(Type B-1); Convective Heat:(Type A-
2);(Type B--); Small Splashes:(Type A-3);(Type B-2); Dexterity:(Type A-1 (11));(Type B-4 (6.5))
Type B gloves are recommended when high dexterity is required as for TIG welding, while type A gloves
are recommended for other welding processes. The contact temp (oC) is 100 and the threshold time
(seconds) >15.

Other

Other

Avoid exposure to welding fumes, radiation, spatter, electric shock, heated materials and dust. Train welders to avoid contact with live electrical parts and insulate conductive parts.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

Ventilation Ensure sufficient ventilation, local exhaust, or both, to keep welding fumes and gases from breathing zone and general area. Use special care when welding painted or coated steels since hazardous paustances from the coating may be emitted. Use respirator or air supplied respirator when welding or brazing in a confined space, or where local exhaust or ventilation is not sufficient to keep exposure values within safe limits.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid, non-volatile with varying color.
Colour	No data available
Odour	No data available
Melting point / freezing point	>1000°C / >1800oF
Boiling point or initial boiling point and boiling range	No data available
Flammability	No data available
Lower and upper explosion limit	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
рН	No data available
Kinematic viscosity	No data available
Solubility	No data available
Partition coefficient n- octanol/water	No data available
Vapour pressure	No data available
Density and/or relative density	No data available
Relative vapour density	No data available
9.2. Other information	
	No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

10.2. Chemical stability	
Chemical stability	Stable at normal conditions
10.3. Possibility of hazardous re	eactions
	No data available
10.4. Conditions to avoid	
Conditions to avoid	This product is only intended for normal welding purposes.
10.5. Incompatible materials	
	No data available
10.6. Hazardous decompositior	n products
Hazardous decomposition products	When this product is used in a welding process, hazardous decomposition products would include those from the volatilization, reaction or oxidation of the materials listed in Section 3 and those from the base metal / Coated wire / Coated rod / Bare wire / Bare rod.
Other	
Other	Refer to applicable national exposure limits for fume compounds, including those exposure limits for fume compounds found in Section 8. Manganese has a low exposure limit, in some countries, that may be easily exceeded. Reasonably expected gaseous products would include carbon oxides, nitrogen oxides and ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quantity of fumes and gases produced.

SECTION 11: Toxicological information

CAS / EC no. NICKEL POWDER**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on toxicological effects	Inhalation of welding fumes and gases ca is difficult because of varying base mater The International Agency for Research of humans (Group 1).	ials, coatings, air contamination	and processes.
Acute toxicity	Acute toxicity: Overexposure to welding f nausea, dryness or irritation of the nose,	• • •	e metal fume fever, dizziness,
Skin corrosion/irritation	No data available.		
Serious eye damage/irritation	No data available.		
Respiratory or skin sensitisation	No data available.		
Germ cell mutagenicity	No data available.		
Genotoxicity	No data available.		
Carcinogenicity			
Product / Substance name	Other		

**This product contains substance(s) that may cause cancer, which

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

Product / Substance name CAS / EC no.		Other
7440-02-0 / 231-111-4		is/are classified as Possibly carcinogenic to humans as per IARC. This product can expose you to Nickel Powder which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.
Repeated dose toxicity	No data available.	
Reproductive toxicity	No data available.	
STOT-single exposure	No data available.	
STOT-repeated exposure	No data available.	
Aspiration hazard	No data available.	
LD50 Oral	No data available.	
LD50 Dermal	No data available.	
LC50 Inhalation	No data available.	
11.2. Information on other haza	rds	
	No data available	
Other		
Long term effect	,	o welding fumes may affect pulmonary function. Prolonged inhalation of posure limits can cause cancer. Overexposure to manganese and

nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait.

manganese compounds above safe exposure limits can cause irreversible damage to the central

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity	No data available.
Toxicity	No data available.
Aquatic	No data available.
Soil	No data available.
Acute fish toxicity	No data available.
Acute algae toxicity	No data available.
Acute crustacean toxicity	No data available.
Chronical toxicity	

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Product / Substance name CAS / EC no.		Remark
NICKEL POWDER** 7440-02-0 / 231-111-4		This product contains Nickel powder which is classified as harmful to aquatic organisms by 1272/2008 CLP Directive and may cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradal	bility	
Persistence and degradability	No data available.	
Decay/transformation	No data available.	
12.3. Bioaccumulative potential	,	
Bioaccumulative potential	No data available.	
12.4. Mobility in soil		
Mobility	No data available.	
12.5. Results of PBT and vPvB	assessment	
Results of PBT and vPvB assessment	No data available.	
12.6. Endocrine disrupting prop	erties	
	No data available	
12.7. Other adverse effects		
Other adverse effects	No data available.	
Other		
Other		rials could degrade/weather into components originating from the als used in the welding process. Avoid exposure to conditions that could roundwater.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	3
Disposal considerations	Discard any product, residue, disposable container or liner in an environmentally acceptable manner, in full compliance with federal and local regulations. Use recycling procedures if available. USA RCRA: This product is not considered hazardous waste if discarded. Residues from welding consumables and processes could degrade and accumulate in soils and groundwater.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Issued: 2022-06-17

SECTION 14: Transport information

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 EU regulations concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL. of 19 November 2008. on waste and repealing certain Directives. European Parliament and Council Directive 94/62/EC of 20 December 1994 on packaging and packaging waste.

This Safety Data Sheet complies with Annex II of 830/2015 amending EC No. 1907/2006,Commision Regulation (EU) 2020/878 amending CLP directive 1272/2008, also in accordance with ISO 11014-1 and ANSI Z400.1

Other regulations, limitations	Poland Regulations:
and legal regulations	ACT of 25 February 2011 on the chemical substances and their mixtures(OJ # 63, poz. 322).
	Regulation of the Minister of Family, Labour and Social Policy of 12th June 2018 on the Maximum
ł	Admissible Concentrations and Intensities of Harmful to Health Agents in the Working Environment (Dz
	U. No 1286) The Act on Waste of 14 December 2012, Journal of Laws of 2013, item 21 with
	amendments
	Act of 13th June 2013 on packaging management and packaging waste (Journal of Laws of 2013, item
	888). Regulation of the Minister of the Environment of 9 December 2014 on waste catalogue (Journal o
	Laws of 2014, item 1923). Regulation of the Minister of Economy of 21 December 2005. Concerning
	essential requirements for personal protective equipment (Journal. Laws No. 259, item. 2173).
	Regulation of the Minister of Health of 2 February 2011 on tests and measurements of factors harmful
	health in the working environment (the Journal of Laws 2011, no. 33, item 166).
	USA Regulations :
	USA: This product contains or produces a chemical known to the state of California to cause cancer an
	birth defects (or other reproductive harm). (California Health & Safety Code § 25249.5 et seq.)
	CERCLA/SARA Title III Reportable Quantities (RQs) and/or Threshold Planning Quantities (TPQs):
	Product is a solid solution in the form of a solid article. Spills or releases resulting in the loss of any
	ingredient at or above its RQ require immediate notification to the National Response Center and to you
	Local Emergency Planning Committee.
	EPCRA/SARA Title III 313 Toxic Chemicals: The following metallic components are listed as SARA 313
	"Toxic Chemicals" and potential subject to annual SARA 313 reporting. See Section 3 for weight percent
	Manganese: 1.0% de minimis concentration
	Nickel Powder: 0.1% de minimis concentration
	Aluminum: 1.0% de minimis concentration
	International Inventories:
	Australia: The substance(s) in this product is/are in compliance with the inventory requirements of
	Australia- Inventory of Industrial Chemicals (AIIC)
	United States EPA Toxic Substance Control Act: All constituents of this product are on the TSCA
	inventory list under active substances
	Canadian Environmental Protection Act (CEPA): All constituent(s) of this product is/are on the Domesti
	Substance List (DSL).
5.2. Chemical safety assessme	ent
Chemical safety assessment	Not Available
Dther	
Other	Read and understand the manufacturer's instructions, your employer's safety practices and the health
	and safety instructions on the label. Observe any federal and local regulations. Take precautions wher
	welding and protect yourself and others.
	weiging and protect yoursen and others.
	WARNING Wolding fumon and gapped are bezardeus to your bastill and may demand fumor and the
	WARNING: Welding fumes and gases are hazardous to your health and may damage lungs and other organs. Use adequate ventilation. ELECTRIC SHOCK can kill. ARC RAYS and SPARKS can injure eyes and burn skin.

SECTION 16: Other information

Changes to previous revision This Safety Data Sheet has been revised due to modifications to Sections 1-16. Latest Revision of SDS as per Regulation and exposure limits – October 2021.

	SAFETY DATA SHEET
	This Safety Data Sheet complies with Annex II of
	830/2015 amending EC No.
Issue	1907/2006,Commision Regulation (EU) 2020/878
	amending CLP directive 1272/2008, also in
	accordance with ISO 11014-1 and ANSI Z400.1

References to key literature and data sources	Refer to ESAB "Welding and Cutting - Risks and Measures", F52-529 "Precautions and Safe Practices for Electric Welding and Cutting" and F2035 "Precautions and Safe Practices for Gas Welding, Cutting and Heating" available from ESAB, and to: www.esab.com USA: Contact ESAB at www.esabna.com or 1-800 ESAB-123 if you have any questions about this SDS. American National Standard Z49.1 "Safety i Welding and Cutting", ANSI/AWS F1.5 "Methods for Sampling and Analyzing Gases from Welding and Allied Processes", ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes", AWSF3.2M/F3.2 "Ventilation Guide for Weld Fume", American Welding Society, 550 North Le Jeune Road, Miami Florida 33135. Safety and Health Fact Sheets available from AWS at www.aws.org. OSHA Publication 2206 (29 C.F.R. 1910), U.S. Government Printing Office, Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954 American Conference of Governmental Hygienists (ACGIH), Threshold Limit Values and Biological Exposure Indices, 6500 Glenway Ave., Cincinnati, Ohio 45211, USA. NFPA 51B "Standard for Fire Prevention During Welding, Cutting, and Other Hot Work" published by the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169. UK: WMA Publication 236 and 237, "Hazards from Welding Fume", "The arc welder at work, some general aspects of health and safety". Germany: Accident prevention regulation BGV D1, "Welding, cutting and related procedures". Canada: CSA Standard CAN/CSA-W117.2-01 "Safety in Welding, Cutting, and Allied Processes". This product has been classified according to the hazard criteria of the CPR and the SDS contains all th information required by the CPR.
Phrase meaning	Acute Tox. 3 - dermal - Acute toxicity, dermal, hazard category 3 Skin Sens. 1 - Skin sensitisation, hazard category 1 Carc. 2 - Carcinogenicity, hazard category 2 STOT RE 1 - Specific Target Organ Toxicity — Repeated exposure, hazard category 1 Aquatic Chronic 3 - Hazardous to the aquatic environment — Chronic hazard category 3 H311 Toxic in contact with skin. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H372 Causes damage to organs through prolonged or repeated exposure . H412 Harmful to aquatic life with long lasting effects.
Other	
Additional information	WELDING MATERIAL SALES, INC requests the users of this product to study this Safety Data Sheet (SDS) and become aware of product hazards and safety information. To promote safe use of this product a user should:
	 Notify its employees, agents and contractors of the information on this SDS and any product hazards/safety information. Furnish this same information to each of its customers for this product. Request such customers to notify employees and customers for the same product hazards and safety information. The information herein is given in good faith and based on technical data that WELDING MATERIAL SALES, INC believes to be reliable. Since the conditions of use is outside our control, we assume no liability in connection with any use of this information and no warranty, expressed or implied is given. Contact WELDING MATERIAL SALES, INC for more information.