



FICHA DE DATOS DE SEGURIDAD

Esta hoja de datos de seguridad (SDS) es para consumibles de soldadura y productos relacionados y se puede usar para cumplir con el estándar de comunicación de peligros de OSHA, 29 CFR 1910.1200, y la Ley de enmiendas y reautorización del super fondo (SARA) de 1986 Ley pública 99-499 y peligros del lugar de trabajo canadiense Sistema de información de materiales (WHMIS) según la política administrativa de Health Canada. Se debe consultar la norma OSHA para conocer los requisitos específicos. Esta hoja de datos de seguridad cumple con las normas ISO 11014-1 y ANSI Z400.1.

Nombre del fabricante/
proveedor: WELDING MATERIAL SALES
DIRECCIÓN: 3940 Stern Ave St. Charles IL 60174
Teléfono no: +1 630-232-6421
Número de emergencia: +1 800-424-9300
Correo electrónico: sales@weldingmaterialsales.com

Sitio web: www.weldingmaterialsales.com

Tipo de producto: GAS METAL ARC WELDING (GMAW) STAINLESS WIRE AND GAS TUNGSTEN ARC WELDING (GTAW)
STAINLESS WIRE

Nombre comercial: 307L HiSiL, 308,308H,308L, 308L HiSiL, 309,309(H),309L,309L HiSiL, 310,316,316L,316L HiSiL, 347,410, 410NiMo, 317L,630,312,2209

Especificaciones de AWS: A5.9 - (ER307LSi),ER308,ER308H, ER308L,ER308LSi, ER309, ER309(H),ER309L, ER309LSi,ER 310, ER316,ER316L,ER316LSi,ER347, ER410, ER410NiMo,ER317L,ER630,ER312, ER2209 ,ER409Nb,ER330, ER320LR,ER2553

Uso recomendado: GAS METAL ARC WELDING (GMAW) STAINLESS WIRE AND GAS TUNGSTEN ARC WELDING (GTAW) STAINLESS WIRE

Restricciones de uso: Use only as indicated for welding operations

SECCIÓN 2 - IDENTIFICACIÓN DE PELIGROS

CLASIFICACIÓN DE PELIGROS - Los productos descritos en la Sección 1 no están clasificados como peligrosos de acuerdo con los criterios de clasificación de peligros del GHS aplicables según lo requerido y definido en el Estándar de comunicación de peligros de OSHA (29 CFR Parte 1910.1200).

ELEMENTOS DE LA ETIQUETA: Símbolo de peligro - No se requiere ningún símbolo
Palabra de advertencia - No se requiere palabra de advertencia
Declaración de peligro - No aplicable
Declaración de precaución - No aplicable

PELIGROS NO CLASIFICADOS DE OTRO MODO

¡ADVERTENCIA! - Evite respirar los humos y gases de soldadura, pueden ser peligrosos para su salud. Utilice siempre una ventilación adecuada. Utilice siempre el equipo de protección personal adecuado.

RUTAS PRINCIPALES DE ENTRADA: Sistema Respiratorio, Ojos y/o Piel.

RAYOS DEL ARCO: El arco de soldadura puede lesionar los ojos y quemar la piel.

DESCARGA ELÉCTRICA: La soldadura por arco y los procesos asociados pueden causar la muerte. Consulte la Sección 8.

HUMOS Y GASES: Puede ser peligroso para su salud.

Los humos y gases de soldadura no pueden clasificarse de forma sencilla. La composición y la cantidad de ambos dependen del metal que se suelda, el proceso, los procedimientos y los electrodos utilizados. La mayoría de los ingredientes de los humos están presentes como óxidos y compuestos complejos y no como metales puros. Cuando se consume el electrodo, los productos de descomposición de humos y gases generados son diferentes en porcentaje y forma de los ingredientes enumerados en la Sección 3. Los productos de descomposición del funcionamiento normal incluyen los que se originan de la volatilización, reacción u oxidación, más los del metal base y recubrimiento, etc., de los materiales que se muestran en la Sección 3 de esta Hoja de Datos de Seguridad. Supervise los materiales componentes identificados en la lista de la Sección 3.

Los humos del uso de este producto pueden contener óxidos complejos o compuestos de los siguientes elementos y moléculas: humo de sílice amorfa, cromo, manganeso y níquel. Otros constituyentes razonablemente esperados del humo también incluirían óxidos complejos de hierro, silicio y molibdeno. Los productos de reacción gaseosos pueden incluir monóxido de carbono y dióxido de carbono. La radiación del arco puede formar ozono y óxidos de nitrógeno. Otras condiciones que también influyen en la composición y cantidad de los humos y gases a los que pueden estar expuestos los trabajadores incluyen: los revestimientos del metal que se suelda (como pintura, enchapado o galvanizado), el número de soldadores y el volumen del área de trabajo, la calidad y cantidad de ventilación, la posición de la cabeza del soldador con respecto a la columna de humo, así como la presencia de contaminantes en la atmósfera (como vapores de hidrocarburos clorados de las actividades de limpieza y desengrasado). Una forma recomendada de determinar la composición y la cantidad de humos y gases a los que están expuestos los trabajadores es tomar una muestra de aire dentro del casco del soldador, si lo lleva puesto, o en la zona de respiración del trabajador. Consulte ANSI/AWS Fl.1 y Fl.3, disponibles en la "American Welding Society", 8669 NW 36 Street, # 130, Miami, Florida 33166-6672, Teléfono: 800-443-9353 o 305-443-9353.

SECCIÓN 3 - INFORMACIÓN SOBRE LA COMPOSICIÓN DE LOS INGREDIENTES

INGREDIENTES PELIGROSOS

IMPORTANTE: esta sección cubre los materiales peligrosos con los que se fabrica este producto. Estos datos han sido clasificados de acuerdo con los criterios del Sistema Globalmente Armonizado de Clasificación y Etiquetado de Químicos (GHS) según lo requerido y definido en el Estándar de Comunicación de Riesgos de OSHA (29 CFR Parte 1910.1200). Los humos y gases producidos durante la soldadura con el uso normal de este producto se abordan en la Sección 8.

INGREDIENTE	NO CAS.	EINECS ^r	%Peso	Clasificación(es) GHS	DECLARACIONES DE PELIGRO DEL SGA (Consulte la Sección 16 para las frases de Comolete)
CROMO (metal)	7440-47-3	231-157-5	5-35	NINGUNO	
COBRE	7440-50-8	231-159-6	0-4 ⁽¹⁾	NINGUNO	
HIERRO	7439-89-6	231-096-4	40-90	NINGUNO	
MANGANESO	7439-96-5	231-105-1	0-5	- Toxicidad aguda 4 (Inhalación) ⁽²⁾ - Toxicidad aguda 4 (Oral) ⁽²⁾ - STOT RE 1 ⁽³⁾	H332 H302 H372
MOLIBDENO	7439-98-7	231-107-2	0-4	- STOT RE 2 ⁽³⁾ - Irritación ocular. 2 ⁽⁴⁾ - STOT SE 3 ⁽⁵⁾	H373 H319 H335



FICHA DE DATOS DE SEGURIDAD

NÍQUEL	7440-02-0	231-111-4	0-40	Polvo/Elemento: - Carc. 2(6) - Sensibilidad de la piel 1(7) - STOT RE 1(8) - Crónica acuática 3	H351 H317 H372 H412
NIOBIO	7440-03-1	231-113-5	0-1(8)	NONE	
(Amorphous Silica Fume)	69012-64-2	273-761-1	---	NONE	
SILICON	7440-21-3	231-130-8	0-1	NONE	
HEXAVALENT CHROMIUM [CHROMIUM (VI) TRIOXIDE] (Fume constituent)	1333-82-0	215-607-8	Varies	- Ox. Sol. 1(9) - Carc. 1A(6) - Muta. 1B(10) - Repr. Tox. 2(11) - Acute Tox. 2 (Inhalation)(2) - Acute Tox. 3 (Skin & Oral)(2) - STOT RE 1(3) - Skin Corr. 1A(12) - Skin Sens. 1(7) - Resp. Sens. 1(13) - Aquatic Acute 1 - Aquatic Chronic 1	H271 H350 H340 H361f H330 H311, H301 H372 H314 H317 H334, H317 H400 H410

--- Dashes indicate the ingredient is not present within the group of products F – European Inventory of Existing Commercial Chemical Substances Number (1) Present only in ER630 (2) Acute toxicity (Cat. 1, 2, 3 and 4) (3) Specific target organ toxicity (STOT) – repeated exposure (Cat. 1 and 2) (4) Serious eye damage/eye irritation (Cat. 1 and 2) (5) Specific target organ toxicity (STOT) – single exposure ((Cat. 1, 2) and Cat. 3 for narcotic effects and respiratory tract irritation, only (6) Carcinogenicity (Cat. 1A, 1B and 2) (7) Skin sensitization (Cat. 1, Sub-cat. 1A and 1B) (8) Present only in ER347 and ER630 (9) Oxidizing solid (Cat. 1, 2 and 3) (10) Germ cell mutagenicity (Cat. 1A, 1B and 2) (11) Reproductive toxicity (Cat. 1A, 1B and 2) (12) Skin corrosion/irritation (Cat. 1, 1A, 1B, 1C and 2) (13) Respiratory sensitization (Cat. 1, Sub-cat. 1A and 1B)

SECTION 4 – FIRST AID MEASURES

INGESTION: Not an expected route of exposure. Do not eat, drink, or smoke while welding; wash hands thoroughly before performing these activities. If symptoms develop, seek medical attention at once.

INHALATION during welding: If breathing is difficult, provide fresh air and contact physician. If breathing has stopped, perform artificial respiration and obtain medical assistance at once.

SKIN CONTACT during welding: Remove contaminated clothing and wash the skin thoroughly with soap and water. If symptoms develop, seek medical attention at once.

EYE CONTACT during welding: Dust or fume from this product should be flushed from the eyes with copious amounts of clean, tepid water until victim is transported to an emergency medical facility. Do not allow victim to rub or keep eyes tightly closed. Obtain medical assistance at once.

Arc rays can injure eyes. If exposed to arc rays, move victim to dark room, remove contact lenses as necessary for treatment, cover eyes with a padded dressing and rest. Obtain medical assistance if symptoms persist.

Section 11 of this SDS covers the acute effects of overexposure to the various ingredients within the welding consumable. Section 8 of this SDS lists the exposure limits and covers methods for protecting yourself and your co-workers.

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazards: Welding consumables applicable to this sheet as shipped are nonreactive, nonflammable, non-explosive and essentially nonhazardous until welded.

Welding arcs and sparks can ignite combustibles and flammable products. If there are flammable materials, including fuel or hydraulic lines, in the work area and the worker cannot move the work or the flammable material, a fire-resistant shield such as a piece of sheet metal or fire resistant blanket should be placed over the flammable material. If welding work is conducted within 35 feet or so of flammable materials, station a responsible person in the work zone to act as fire watcher to observe where sparks are flying and to grab an extinguisher or sound the alarm if needed.

Unused welding consumables may remain hot for a period of time after completion of a welding process. See American National Standard Institute (ANSI) Z49.1 for further general safety information on the use and handling of welding consumables and associated procedures.

Suitable Extinguishing Media: This product is essentially nonflammable until welded; therefore, use a suitable extinguishing agent for a surrounding fire.

Unsuitable Extinguishing Media: None known.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

In the case of a release of solid welding consumable products, solid objects can be picked up and placed into a disposal container. If airborne dust and/or fume is present, use adequate engineering controls and, if needed, personal protection to prevent overexposure. Refer to recommendations in Section 8. Wear proper personal protective equipment while handling. Do not discard as general trash.

SECTION 7 - HANDLING AND STORAGE

HANDLING: No specific requirements in the form supplied. Handle with care to avoid cuts. Wear gloves when handling welding consumables. Avoid exposure to dust. Do not ingest. Some individuals can develop an allergic reaction to certain materials. Retain all warning and product labels.

STORAGE: Keep separate from acids and strong bases to prevent possible chemical reactions.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Read and understand the instructions and the labels on the packaging. Welding fumes do not have a specific OSHA PEL (Permissible Exposure Limit) or ACGIH TLV (Threshold Limit Value). The OSHA PEL for Particulates – Not Otherwise Regulated (PNOR) is 5 mg/m³ – Respirable Fraction, 15 mg/m³ – Total Dust. The ACGIH TLV for Particles – Not Otherwise Specified (PNOS) is 3 mg/m³ – Respirable Particles, 10 mg/m³ – Inhalable Particles. The individual complex compounds within the fume may have a lower OSHA PEL or ACGIH TLV than the OSHA PNOR and ACGIH PNOS. An Industrial Hygienist, the OSHA PELs for Air Contaminants (29 CFR 1910.1000), and the ACGIH TLVs should be consulted to determine the specific fume constituents present and their respective exposure limits. All exposure limits are in milligrams per cubic meter (mg/m³).



SAFETY DATA SHEET

INGREDIENT	CAS	EINECS	OSHA PEL	ACGIH TLV
CHROMIUM#	7440-47-3	231-157-5	1 (Metal) 0.5 (Cr II & Cr III Cpnds) 0.005 (Cr VI Cpnds, Calif. OSHA PEL)	0.5 (Metal) 0.003 (Cr III Cpnds) (A4; DSEN; RSEN) 0.0002 (Cr VI Sol Cpnds) {A1; Skin; DSEN; RSEN} 0.0005 (Cr VI STEL)
COPPER	7440-50-8	231-159-6	0.1 (Fume), 1 (Dust)	0.2 (Fume), 1 (Dust)
IRON+	7439-89-6	231-096-4	5 R*	5 R* (Fe ₂ O ₃) {A4}
IRON OXIDE	1309-37-1	215-168-2	10 (Oxide Fume)	5R*(Fe ₂ O ₃) {A4}
MANGANESE#	7439-96-5	231-105-1	5 CL** (Fume) 1, 3 STEL***■	0.1 I* {A4} ◆ 0.02 R* ◆◆
MOLYBDENUM	7439-98-7	231-107-2	5 R*	3 R*; 10 I* (Ele and Insol) 0.5 R* (Sol Cpnds) {A3}
NICKEL#	7440-02-0	231-111-4	1 (Metal) 1 (Sol Cpnds) 1 (Insol Cpnds)	1.5 I* (Ele) {A5} 0.1 I* (Sol Cpnds) {A4} 0.2 I* (Insol Cpnds) {A1}
NIOBIUM+	7440-03-1	231-113-5	Not Established	Not Established
(Amorphous Silica Fume)	69012-64-2	273-761-1	0.8	2 R*
SILICON+	7440-21-3	231-130-8	5 R*	3 R*

R* - Respirable Fraction I* - Inhalable Fraction ** - Ceiling Limit *** - Short Term Exposure Limit +- As a nuisance particulate covered under "Particulates Not Otherwise Regulated" by OSHA or "Particulates Not Otherwise Specified" by ACGIH ++ - Crystalline silica is bound within the product as it exists in the package. However, research indicates silica is present in welding fume in the amorphous (noncrystalline) form #- Reportable material under Section 313 of SARA ■ - NIOSH REL TWA and STEL ◆ - Limit of 0.1 mg/m³ is for inhalable Mn in 2015 by ACGIH ◆◆ - Limit of 0.02 mg/m³ is for Respirable Mn in 2015 by ACGIH Ele - Element Sol - Soluble Insol - Insoluble Inorg - Inorganic Cpnds - Compounds NOS - Not Otherwise Specified {A1} - Confirmed Human Carcinogen per ACGIH {A2} - Suspected Human Carcinogen per ACGIH {A3} - Confirmed Animal Carcinogen with Unknown Relevance to Humans per ACGIH {A4} - Not Classifiable as a Human Carcinogen per ACGIH {A5} - Not Suspected as a Human Carcinogen per ACGIH (noncrystalline form) DSEN - Dermal Sensitization RSEN - Respiratory Sensitization EINECS - European Inventory of Existing Commercial Chemical Substances OSHA - U.S. Occupational Safety and Health Administration ACGIH - American Conference of Governmental Industrial Hygienists

VENTILATION: Use enough ventilation or local exhaust at the arc or both to keep the fumes and gases below the PEL/TLV in the worker's breathing zone and the general area. Train the welder to keep his head out of the fumes.

RESPIRATORY PROTECTION: Use NIOSH-approved or equivalent fume respirator or air supplied respirator when welding in confined space or where local exhaust or ventilation does not keep exposure below the regulatory limits.

EYE PROTECTION: Wear helmet or use face shield with filter lens for open arc welding processes. As a rule of thumb begin with Shade Number 14. Adjust if needed by selecting the next lighter and/or darker shade number. Provide protective screens and flash goggles, if necessary, to shield others from the weld arc flash.

PROTECTIVE CLOTHING: Wear hand, head and body protection which help to prevent injury from radiation, sparks and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection as well as dark non-synthetic clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground.

PROCEDURE FOR CLEANUP OF SPILLS OR LEAKS: Not applicable

SPECIAL PRECAUTIONS (IMPORTANT): When welding with electrodes that require special ventilation (such as stainless or hardfacing, or other products which require special ventilation, or on lead- or cadmium-plated steel and other metals or coatings like galvanized steel, which produce hazardous fumes) maintain exposure below the PEL/TLV. Use industrial hygiene monitoring to ensure that your use of this material does not create exposures which exceed PEL/TLV. Always use exhaust ventilation. Refer to the following sources for important additional information: American National Standard Institute (ANSI) Z49.1; Safety in Welding and Cutting published by the American Welding Society, 8669 NW 36 Street, # 130, Miami, Florida 33166-6672, Phone: 800-443-9353 or 305-443-9353; and OSHA Publication 2206 (29 CFR 1910), U.S. Government Printing Office, Washington, DC 20402.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Welding consumables applicable to this sheet as shipped are nonreactive, nonflammable, non-explosive and essentially nonhazardous until welded.

PHYSICAL STATE: Solid

APPEARANCE: Round, solid wire or rod

COLOR: Gray

ODOR: Not Applicable

ODOR THRESHOLD: Not Applicable

pH: Not Applicable

MELTING POINT/FREEZING POINT: Not Available

INITIAL BOILING POINT AND BOILING RANGE: Not Available

FLASH POINT: Not Available

EVAPORATION RATE: Not Applicable

FLAMMABILITY (SOLID, GAS): Not Available

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS: Not Available

VAPOR PRESSURE: Not Applicable

VAPOR DENSITY: Not Applicable

RELATIVE DENSITY: Not Available

SOLUBILITY(IES): Not Available

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Applicable

AUTO-IGNITION TEMPERATURE: Not Available

DECOMPOSITION TEMPERATURE: Not Available

VISCOSITY: Not Applicable

SECTION 10 - STABILITY AND REACTIVITY

GENERAL: Welding consumables applicable to this sheet are solid and nonvolatile as shipped. This product is only intended for use per the welding parameters it was designed for. When this product is used for welding, hazardous fumes may be created. Other factors to consider include the base metal, base metal preparation and base metal coatings. All of these factors can contribute to the fume and gases generated during welding. The amount of fume varies with the welding parameters.

STABILITY: This product is stable under normal conditions.

REACTIVITY: Contact with acids or strong bases may cause generation of gas.

SECTION 11 - TOXICOLOGICAL INFORMATION

SHORT-TERM (ACUTE) OVEREXPOSURE EFFECTS: Welding Fumes - May result in discomfort such as dizziness, nausea or dryness or irritation of nose, throat or eyes. **Chromium** - Inhalation of fume with chromium (VI) compounds can cause irritation of the respiratory tract, lung damage and asthma-like symptoms. Swallowing chromium (VI) salts can cause severe injury or death. Dust on skin can form ulcers. Eyes may be burned by chromium (VI) compounds. Allergic reactions may occur in some people. **Copper** - Metal fume fever characterized by metallic taste, tightness of chest and fever. Symptoms may last 24 to 48 hours following overexposure. **Iron, Iron Oxide** - None are known. Treat as nuisance dust or fume. **Manganese** - Metal fume fever characterized by chills, fever, upset stomach, vomiting, irritation of the throat and aching of body. Recovery is generally complete within 48 hours of the overexposure. **Molybdenum** - Irritation of the eyes, nose and throat. **Nickel, Nickel Compounds** - Metallic taste, nausea, tightness in chest, metal



SAFETY DATA SHEET

fume fever, allergic reaction. **Niobium** - Dust or fumes may cause irritation of the respiratory system, skin and eyes. **Silica (Amorphous)** - Dust and fumes may cause irritation of the respiratory system, skin and eyes.

LONG-TERM (CHRONIC) OVEREXPOSURE EFFECTS: **Welding Fumes** - Excess levels may cause bronchial asthma, lung fibrosis, pneumoconiosis or "siderosis." Studies have concluded that there is sufficient evidence for ocular melanoma in welders. **Chromium** - Ulceration and perforation of nasal septum. Respiratory irritation may occur with symptoms resembling asthma. Studies have shown that chromate production workers exposed to hexavalent chromium compounds have an excess of lung cancers. Chromium (VI) compounds are more readily absorbed through the skin than chromium (III) compounds. Good practice requires the reduction of employee exposure to chromium (III) and (VI) compounds. **Copper** - Copper poisoning has been reported in the literature from exposure to high levels of copper. Liver damage can occur due to copper accumulating in the liver characterized by cell destruction and cirrhosis. High levels of copper may cause anemia and jaundice. High levels of copper may cause central nervous system damage characterized by nerve fiber separation and cerebral degeneration. **Iron, Iron Oxide Fumes** - Can cause siderosis (deposits of iron in lungs) which some researchers believe may affect pulmonary function. Lungs will clear in time when exposure to iron and its compounds ceases. Iron and magnetite (Fe3O4) are not regarded as fibrogenic materials. **Manganese** - Long-term overexposure to manganese compounds may affect the central nervous system. Symptoms may be similar to Parkinson's disease and can include slowness, changes in handwriting, gait impairment, muscle spasms and cramps and less commonly, tremor and behavioral changes. Employees who are overexposed to manganese compounds should be seen by a physician for early detection of neurologic problems. Overexposure to manganese and manganese compounds above safe exposure limits can cause irreversible damage to the central nervous system, including the brain, symptoms of which may include slurred speech, lethargy, tremor, muscular weakness, psychological disturbances and spastic gait. **Molybdenum** - Prolonged overexposure may result in loss of appetite, weight loss, loss of muscle coordination, difficulty in breathing and anemia. **Nickel, Nickel Compounds** - Lung fibrosis or pneumoconiosis. Studies of nickel refinery workers indicated a higher incidence of lung and nasal cancers. **Niobium** - No adverse long term health effects have been reported in the literature. **Silica (Amorphous)** - Research indicates that silica is present in welding fume in the amorphous form. Long term overexposure may cause pneumoconiosis. Non-crystalline forms of silica (amorphous silica) are considered to have little fibrotic potential.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Persons with pre-existing impaired lung functions (asthma-like conditions). Persons with a pacemaker should not go near welding and cutting operations until they have consulted their doctor and obtained information from the manufacturer of the device. Respirators are to be worn only after being medically cleared by your company-designated physician.

EMERGENCY AND FIRST AID PROCEDURES: Call for medical aid. Employ first aid techniques recommended by the American Red Cross. If irritation or flash burns develop after exposure, consult a physician.

CARCINOGENICITY: Chromium VI compounds and nickel compounds are classified as IARC Group 1 and NTP Group K carcinogens. Welding fumes are classified as IARC Group 2B carcinogens.

CALIFORNIA PROPOSITION 65:

WARNING: These products can expose you to chemicals, including titanium dioxide and/or chromium and/or nickel, which are known to the State of California to cause cancer, and to carbon monoxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

INGREDIENT	CAS	IARC ^E	NTP ^Z	OSHA ^H	65 ^O
CHROMIUM	7440-47-3	3 ^F , 1 ^{ZZ}	K ^{ZZ}	X ^{ZZ}	X ^{ZZ}
COPPER	7440-50-8	---	---	---	---
IRON	7439-89-6	---	---	---	---
IRON OXIDE	1309-37-1	3	---	---	---
MANGANESE	7439-96-5	---	---	---	---
MOLYBDENUM	7439-98-7	---	---	---	---
NICKEL	7440-02-0	2B ^B , 1 ^{B^B}	5 ^B , K ^{B^B}	--	X ^B , X ^{B^B}
NIOBIUM	7440-03-1	---	---	---	---
(Amorphous Silica fume)	69012-64-2	3	---	---	---
SILICON	7440-21-3	---	---	---	---
Ultraviolet Radiation	---	1	---	---	---
Welding Fumes	---	1	---	---	---

E – International Agency for Research on Cancer (1 – Carcinogenic to Humans, 2A – Probably Carcinogenic to Humans, 2B – Possibly Carcinogenic to Humans, 3 – Not Classifiable as to its Carcinogenicity to Humans, 4 – Probably Not Carcinogenic to Humans) Z – US National Toxicology Program (K – Known Carcinogen, S – Suspected Carcinogen) H – OSHA Designated Carcinogen List O – California Proposition 65 (X – On Proposition 65 list) Σ – Chromium Metal and Chromium III Compounds ΣΣ – Chromium VI β – Nickel metal and alloys ββ – Nickel compounds --- Dashes indicate the ingredient is not listed with the IARC, NTP, OSHA or Prop 65

SECTION 12 – ECOLOGICAL INFORMATION

Welding processes can release fumes directly to the environment. Welding wire can degrade if left outside and unprotected. Residues from welding consumables and processes could degrade and accumulate in the soil and groundwater.

SECTION 13 – DISPOSAL CONSIDERATIONS

Use recycling procedures if available. Discard any product, residue, packaging, disposable container or liner in an environmentally acceptable manner, in full compliance with federal, state and local regulations.

SECTION 14 – TRANSPORT INFORMATION

No international regulations or restrictions are applicable. No special precautions are necessary.

SECTION 15 – REGULATORY INFORMATION

Read and understand the manufacturer's instructions, your employer's safety practices and the health and safety instructions on the label and the safety data sheet. Observe all local and federal rules and regulations. Take all necessary precautions to protect yourself and others.

United States EPA Toxic Substance Control Act: All constituents of these products are on the TSCA inventory list or are excluded from listing.

CERCLA/SARA TITLE III: Reportable Quantities (RQs) and/or Threshold Planning Quantities (TPQs):

Ingredient name	RQ(lb)	TPQ (lb)
Products on this SDS are a solid solution in the form of a solid article.	---	---

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center and to your Local Emergency Planning Committee.



Revised 8/2018
Reviewed 7/2020
SDS #901

SAFETY DATA SHEET

Section 311 Hazard Class

As shipped: Immediate
In use: Immediate delayed

EPCRA/SARA TITLE III 313 TOXIC CHEMICALS: The following metallic components are listed as SARA 313 "Toxic Chemicals" and potentially subject to annual SARA 312 reporting: Chromium, , Copper, Manganese and Nickel. See Section 3 for weight percentage.

CANADIAN WHMIS CLASSIFICATION: Class D; Division 2, Subdivision A

CANADIAN CONTROLLED PRODUCTS REGULATION: This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA): All constituents of these products are on the Domestic Substance List (DSL).

SECTION 16 – OTHER INFORMATION

The following Hazard Statements, provided in the OSHA Hazard Communication Standard (29 CFR Part 1910.1200) correspond to the columns labeled 'GHS Hazard Statements' within Section 3 of this safety data sheet. Take appropriate precautions and protective measures to eliminate or limit the associated hazard.

H271: May cause fire or explosion; strong oxidizer
H301: Toxic if swallowed
H302: Harmful if swallowed
H311: Toxic in contact with skin
H314: Causes severe skin burns and eye damage
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H330: Fatal if inhaled
H332: Harmful if inhaled
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335: May cause respiratory irritation
H340: May cause genetic defects
H350: May cause cancer
H351: Suspected of causing cancer
H361f: Suspected of damaging fertility or the unborn child
H372: Causes damage to organs through prolonged or repeated exposure
H373: May cause damage to organs through prolonged or repeated exposure
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects
H412: Harmful to aquatic life with long lasting effects.

For additional information please refer to the following sources:

USA: American National Standards Institute (ANSI) Z49.1 "Safety in Welding and Cutting", ANSI/American Welding Society (AWS) F1.5 "Methods for Sampling and Analyzing Gases from Welding and Allied Processes", ANSI/AWS F1.1 "Method for Sampling Airborne Particles Generated by Welding and Allied Processes", AWSF3.2M/F3.2 "Ventilation Guide for Weld Fume", American Welding Society, 8669 NW 36 Street, # 130, Miami, Florida 33166-6672, Phone: 800-443-9353 or 305-443-9353. Safety and Health Fact Sheets available from AWS at www.aws.org.
OSHA Publication 2206 (29 C.F.R. 1910), U.S. Government Printing Office, Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250-7954.
Threshold Limit Values and Biological Exposure Indices, American Conference of Governmental Industrial Hygienists (ACGIH), 6500 Glenway Ave., Cincinnati, Ohio 45211, USA. NFPA 51B "Standard for Fire Prevention During Welding, Cutting and Other Hot Work" published by the National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169.

Canada: CSA Standard CAN/CSA-W117.2-01 "Safety in Welding, Cutting and Allied Processes".

WELDING MATERIAL SALES, INC strongly recommends the users of this product study this SDS, the product label information and become aware of all hazards associated with welding. WELDING MATERIAL SALES, INC believes this data to be accurate and to reflect qualified expert opinion regarding current research. However, WELDING MATERIAL SALES, INC cannot make any expressed or implied warranty as to this information.